



## CROSS REFERENCE

PBB	HAGER	SELECT	ABH	MCKINNEY	IVES	STANLEY	MARKAR	GALLERY
CH51	790-900	SL 300	A500	MCK FM 300	700	651	FM300	951
CH52CG	~~	SL310	~~	~~	~~	~~	HG310	~~
CH51G	790-905	SL 305	A505	MCK FM 305	705	652	HG305	952
CH51L	790-915	~~	~~	MCK HG 315	~~	653	HG315	953
CH52CL	790-911	SL 311	A511	MCK HG 311	711	656	HG311	956
CH52	790-904	~~	~~	~~	~~	~~	HM304	~~
CH52L	~~	SL306	~~	~~	~~	~~	HG306	~~
CH53	~~	SL 302	A502	MCK FS 302	702	~~	FS302	957
CH53I	~~	~~	~~	~~	~~	~~	FS301	~~
CH54	790-903	SL303	A503	MCK HM 304	~~	654	HS303	954
CH5GB	~~	SL 308	~~	~~	~~	~~	HG308	~~
CH5GS	~~	SL 308	~~	~~	~~	~~	HG308	~~
CH5LB	~~	~~	A538	~~	~~	~~	EG-C-308	~~
CH5LS	~~	~~	~~	~~	~~	~~	EG-C-308	~~
CH5AB	~~	~~	~~	~~	~~	~~	EG-T-308	~~
CH5AS	~~	~~	~~	~~	~~	~~	EG-T-308	~~

### HOW TO ORDER:

1st - 2nd      Digits indicates series  
 3rd            Digit indicates material  
 4th            Digit indicates type  
 5th - 6th     Digits indicates special function  
 7th - 9th     Digits indicates lengths  
 10th          Digit indicates finish  
 11th          Digit indicates options

### EXAMPLE: CH51G85630

CH = Continuous Hinge  
 3 = Aluminum, 5 = Stainless Steel  
 1 = Full Mortise, 2 = Half Mortise, 3 = Full Surface, 4 = Half Surface  
 C = Swing Clear, G=Edge Guard, I = 1/8" Inset,  
 79", 83", 85", 95", 120"  
 630 = Satin Stainless, 629=Polish Stainless Steel  
 E = Concealed Electric Through Wire, EP = Electric Power Transfer

### CONTINUOUS HINGE MODIFICATIONS

- Hospital Tip - Suffix H.
- Dutch Door Prep - Suffix D, indicate handing, clearance, door and frame heights.
- Blank - No holes for special applications. -Suffix K
- Raised Barrel (Swaged) - Suffix R, available for half surface and edge mount models. Required for CH53 to open door 180 degrees.
- Standard Edge Guard Cut-out:
 

4-7/8' ASA Strike	161 Latch	86 Mortise
Manual Flush Bolts	Automatic Flush Bolts	
- Security Stud - Suffix S, stainless steel studs mounted to frame leaf. Corresponding holes drilled in door leaf. Special prep required for frame and door.
- Sheared Leaf - Suffix W for narrow door thickness. Specify distance from pin centerline to heel edge of hinge.
- Custom Hole Pattern - Any hole dimension or pattern other than PBB standard. Indicate hole size and dimensions special hinge configuration with customer supplying the print. Suffix X

### ELECTRICAL MODIFICATIONS

- Concealed Current Transfer - Suffix E (E2, E2+4, E4, E6, E8, E10)
- Lead-Lined Cover - Suffix "L" for surface mount only.
- Electrical Transfer Prep - Suffix EP, indicate positions and handing.

**SCREW PACK #/SECURITY SCREWS** - Spanner Head - Suffix SH or Torx Head - Suffix TH screws available. Refer to product page for screw fastener information.

### For More Information

Contact your local representative or PBB INC., Phone (800) 726-3414 Fax (909) 923-6248

1311 E. Philadelphia Street, Ontario, CA 91761 Web Site: [http:// www.pbbinc.com](http://www.pbbinc.com)

©2009 PBB, Inc All rights reserved 01/09